



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 5-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	5.0Ah
	10 Hour rate	5.0Ah
	5 Hour rate	4.8Ah
Internal Resistance (25°C, 100% Charge)		≤ 25mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		75A (5sec)
Maximum Charging current		2.00A
Short Circuit Current		270A
Charge Methods Constant Voltage Charge 77°F (25°C) - Cycle use		14.4 to 14.7 V Temp. Compensation -30mV/°C
Charge methods Constant Voltage Charge 77°F (25°C) - Standby Use		13.4 to 13.8V Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
90 mm	70 mm	101 mm	107 mm	1.72 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	26.5	17.5	13.0	7.30	4.10	1.55	1.01	0.52	0.27
1.65	25.4	17.2	12.7	7.20	4.02	1.51	0.98	0.51	0.26
1.70	24.3	17.0	12.4	7.13	4.00	1.48	0.97	0.50	0.26
1.75	23.1	16.5	12.1	7.10	3.99	1.44	0.96	0.50	0.25
1.80	21.8	15.8	12.0	7.02	3.98	1.40	0.95	0.50	0.25

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	49.5	35.2	25.7	14.60	8.05	3.05	2.01	-	-
1.65	47.1	34.0	25.2	14.40	8.03	2.99	1.98	-	-
1.70	44.8	33.5	25.0	14.30	8.00	2.93	1.95	-	-
1.75	42.3	32.5	24.3	14.30	7.99	2.86	1.91	-	-
1.80	39.8	31.6	23.5	14.20	7.97	2.80	1.88	-	-




EnerRocketTM
CONTINUOUSLY SAFEGUARDING

ES 5-12


SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**


Discharge Characteristic (25°C)




Constant Voltage Charging characteristics (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge Characteristic




Life Characteristics of standby use




Cycle service life in relation on to depth of discharge



Temperature effect on float life



Temperature effect on capacity





EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 7-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 27°C (80.6°F)	20 Hour rate	7Ah
	10 Hour rate	6.7Ah
	5 Hour rate	5.6Ah
Internal Resistance (25°C, 100% Charge)		25mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		105A (5sec)
Maximum Charging current		2.88A
Short Circuit Current		350A
Charge Methods		14.4 to 14.7 V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
151 mm	65 mm	94 mm	100 mm	2.2 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	30.0	18.8	15.3	8.50	4.80	1.88	1.25	0.66	0.38
1.65	28.4	17.9	14.6	8.15	4.63	1.82	1.20	0.65	0.38
1.70	26.8	17.0	13.9	7.86	4.44	1.76	1.16	0.64	0.37
1.75	25.2	16.0	13.2	7.56	4.25	1.69	1.12	0.63	0.36
1.80	23.5	15.1	12.5	7.18	4.04	1.64	1.10	0.60	0.35

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	53.3	35.8	28.1	15.50	9.30	3.68	2.38	1.34	0.70
1.65	50.7	34.0	27.0	14.90	8.90	3.59	2.34	1.32	0.69
1.70	48.1	32.2	25.9	14.30	8.53	3.49	2.30	1.30	0.68
1.75	45.6	30.4	24.8	13.70	8.28	3.38	2.25	1.28	0.66
1.80	43.1	28.6	23.8	13.20	7.90	3.27	2.19	1.26	0.64




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 7-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 9-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	9.0Ah
	10 Hour rate	8.2Ah
	5 Hour rate	7.7Ah
Internal Resistance (25°C, 100% Charge)		≤ 18 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 50°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		135A
Maximum Charging current		3.6A
Short Circuit Current		450A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
151 mm	65 mm	94 mm	100 mm	2.8 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	33.0	24.2	17.0	9.90	5.80	2.33	1.60	0.87	0.47
1.65	32.1	23.6	16.5	9.79	5.75	2.29	1.56	0.86	0.46
1.70	30.9	22.9	16.1	9.36	5.71	2.25	1.55	0.84	0.46
1.75	30.3	22.1	14.6	8.91	5.66	2.20	1.54	0.82	0.45
1.80	29.6	21.0	13.9	8.45	5.51	2.14	1.53	0.82	0.44

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	71.7	44.8	33.6	19.6	11.5	4.34	3.10	1.70	0.90
1.65	68.3	44.3	33.1	19.1	11.2	4.29	3.04	1.60	0.90
1.70	64.8	42.9	31.1	18.5	11.0	4.20	2.98	1.60	0.90
1.75	61.4	41.1	30.2	17.6	10.7	4.08	2.92	1.60	0.90
1.80	58.0	39.2	28.4	16.6	10.4	3.92	2.85	1.60	0.80




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 9-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 12-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4



TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	12Ah
	10 Hour rate	11.4Ah
	5 Hour rate	10.25Ah
Internal Resistance (25°C, 100% Charge)		≤ 19 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		180A (5sec)
Maximum Charging current		4.8A
Short Circuit Current		600A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
151 mm	98 mm	95mm	101 mm	3.67 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	46.4	31.7	24.8	13.8	8.14	3.18	2.12	1.18	0.61
1.65	45.0	30.8	24.3	13.5	8.04	3.15	2.10	1.17	0.61
1.70	43.5	29.9	23.7	13.3	7.94	3.12	2.07	1.16	0.61
1.75	42.1	29.0	23.2	13.0	7.85	3.09	2.05	1.14	0.60
1.80	40.6	28.2	22.6	12.7	7.75	3.06	2.02	1.12	0.59

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	86.2	58.7	46.7	27.0	16.1	6.50	4.20	2.36	1.22
1.65	84.1	57.7	46.0	26.6	16.0	6.44	4.17	2.33	1.21
1.70	81.9	56.6	45.3	26.2	15.8	6.37	4.14	2.31	1.20
1.75	79.8	55.6	44.6	25.8	15.7	6.31	4.11	2.29	1.18
1.80	77.6	54.6	43.9	25.4	15.5	6.24	4.08	2.26	1.17




EnerRocketTM
CONTINUOUSLY SAFEGUARDING

ES 12-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocketTM
CONTINUOUSLY SAFEGUARDING

ES 18-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	17Ah
	10 Hour rate	16.8Ah
	5 Hour rate	15.05Ah
Internal Resistance (25°C, 100% Charge)		≤ 14 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		225A (5sec)
Maximum Charging current		6.8A
Short Circuit Current		850A
Charge Methods Constant Voltage Charge 77°F (25°C) - Cycle use		14.4 to 14.7V Temp. Compensation -30mV/°C
Charge methods Constant Voltage Charge 77°F (25°C) - Standby Use		13.4 to 13.8V Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
181 mm	77 mm	167 mm	167 mm	5.5 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	67.0	45.1	34.3	20.2	12.0	4.65	3.10	1.70	0.89
1.65	64.6	44.0	33.5	19.8	11.8	4.57	3.05	1.68	0.88
1.70	62.2	42.9	32.6	19.3	11.6	4.49	3.00	1.65	0.87
1.75	59.8	41.7	31.8	18.9	11.3	4.40	2.94	1.63	0.85
1.80	57.4	40.6	30.9	18.4	11.1	4.32	2.89	1.60	0.84

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	117	79.0	61.0	36.0	22.0	9.10	6.16	3.52	1.82
1.65	113	77.4	59.8	35.5	21.8	9.01	6.10	3.49	1.80
1.70	110	75.8	58.5	35.0	21.5	8.92	6.04	3.45	1.78
1.75	106	74.1	57.3	34.5	21.3	8.83	5.98	3.42	1.77
1.80	102	72.5	56.0	34.0	21.0	8.74	5.92	3.38	1.75




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 18-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 26-12

SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	24Ah
	10 Hour rate	23.7Ah
	5 Hour rate	20.5Ah
Internal Resistance (25°C, 100% Charge)		≤ 12 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		300A (5sec)
Maximum Charging current		9.6A
Short Circuit Current		1200A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
166 mm	175 mm	125mm	125 mm	8.1 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	95.0	64.0	48.0	28.5	16.0	6.74	4.47	2.52	1.24
1.65	90.1	60.9	45.9	27.4	15.4	6.53	4.36	2.47	1.23
1.70	84.9	57.8	43.7	26.2	14.8	6.30	4.24	2.42	1.22
1.75	79.7	54.5	41.1	24.9	14.2	6.05	4.10	2.37	1.20
1.80	74.3	51.3	39.1	23.6	13.5	5.78	3.95	2.31	1.18

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	185	121	90.0	55.0	31.7	13.4	8.54	5.38	2.78
1.65	173	114	85.1	52.3	30.3	13.1	8.39	5.35	2.77
1.70	161	107	80.2	49.4	28.9	12.5	8.22	5.30	2.73
1.75	151	99.7	75.2	46.6	27.5	12.0	8.03	5.18	2.68
1.80	139	92.7	70.3	43.7	26.0	11.4	7.83	5.12	2.62




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 26-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 33-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	10 Hour rate	33.0Ah
	5 Hour rate	27.9Ah
	1 Hour rate	22.3Ah
Internal Resistance (25°C, 100% Charge)		≤ 12mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		330A (5sec)
Maximum Charging current		9.9A
Short Circuit Current		850A
Charge Methods Constant Voltage Charge 77°F (25°C) - Cycle use		14.4 to 14.7V Temp. Compensation -30mV/°C
Charge methods Constant Voltage Charge 77°F (25°C) - Standby Use		13.4 to 13.8V Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
195 mm	130 mm	155mm	168 mm	9.7 ± 3%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	90.0	69.3	57.1	32.6	22.3	9.08	6.3	3.36	1.81
1.65	81.0	65.0	54.1	31.3	21.9	8.97	6.25	3.35	1.79
1.70	79.0	60.0	51.4	30.4	21.2	8.45	6.15	3.32	1.78
1.75	67.0	56.1	47.8	29.4	20.3	8.25	5.58	3.31	1.78
1.80	59.5	51.4	44.8	28.8	19.8	8.18	5.50	3.30	1.76

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	144	122	100.0	65.3	40.9	17.4	12.2	6.0	3.2
1.65	140	116	98.6	61.7	40.5	17.3	11.9	5.9	3.2
1.70	135	110	95.7	60.0	39.9	16.8	11.5	5.8	3.2
1.75	126	104	92.0	58.0	39.1	16.0	11.3	5.8	3.1
1.80	119	97.7	89.0	56.0	38.3	15.2	11	5.7	3.1




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 33-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 42-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	42Ah
	10 Hour rate	40Ah
	5 Hour rate	37.55Ah
Internal Resistance (25°C, 100% Charge)		≤ 9.0 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		400A (5sec)
Maximum Charging current		16A
Short Circuit Current		950A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
197 mm	165 mm	170mm	170 mm	12.8 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	130	90.5	72.7	41.9	25.9	11.3	7.95	4.20	2.25
1.65	122	86.2	69.1	40.6	25.4	11.1	7.81	4.15	2.22
1.70	114	81.8	66.5	39.2	24.8	10.9	7.67	4.10	2.18
1.75	106	77.6	63.0	37.7	24.2	10.6	7.51	4.05	2.14
1.80	97	73.9	59.2	36.2	23.5	10.4	7.35	4.00	2.10

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	236	163	127	83.2	50.9	21.5	14.0	8.76	3.9
1.65	220	157	124	81.8	50.2	21.2	13.8	8.59	3.9
1.70	204	150	121	79.3	49.3	20.8	13.6	8.42	3.8
1.75	186	143	117	76.8	48.5	20.5	13.4	8.21	3.8
1.80	177	135	113	74.3	47.7	20.1	13.3	8.04	3.7




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 42-12


SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocketTM
CONTINUOUSLY SAFEGUARDING

ES 55-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 27°C (80.6°F)	10 Hour rate	55.0Ah
	5 Hour rate	46.2Ah
	1 Hour rate	35.1Ah
Internal Resistance (25°C, 100% Charge)		<7.2mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		550A (5sec)
Maximum Charging current		16.5A
Short Circuit Current		1400A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
229 mm	138 mm	208 mm	213 mm	18.0 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	24h
1.60	175	129	99.4	59.2	35.10	14.6	9.82	5.65	2.45
1.65	165	124	95.4	57.4	34.20	14.2	9.57	5.62	2.43
1.70	155	115	90.6	55.6	33.30	13.9	9.40	5.58	2.41
1.75	145	106	85.8	53.8	32.50	13.6	9.23	5.54	2.40
1.80	134	99.8	79.5	51.9	31.70	13.3	9.06	5.50	2.38

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	24h
1.60	318	229	182	111	68.90	29.1	18.8	10.9	5.06
1.65	300	225	177	109	67.30	28.5	18.6	10.8	4.95
1.70	381	213	169	107	65.80	27.9	18.2	10.6	4.85
1.75	261	200	162	105	64.30	27.3	18.0	10.4	4.76
1.80	248	186	154	104	64.00	26.7	17.9	10.2	4.66




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 55-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 65-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4





TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 27°C (80.6°F)	20 Hour rate	68Ah
	10 Hour rate	65Ah
	5 Hour rate	55Ah
Internal Resistance (25°C, 100% Charge)		≤ 6.8 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		650A (5sec)
Maximum Charging current		26A
Short Circuit Current		1700A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
350 mm	167 mm	179mm	179 mm	20.4 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	212	151	126	75.4	45.10	18.4	11.8	6.7	3.48
1.65	201	144	121	73.3	44.00	18	11.6	6.58	3.46
1.70	189	137	115	71.3	43.00	17.6	11.3	6.56	3.44
1.75	177	129	109	69.2	41.90	17.2	11.0	6.53	3.42
1.80	164	120	102	66.9	41.00	16.9	10.7	6.50	3.40

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	378	275	207	129	81.80	33.8	22.5	11.7	6.40
1.65	356	261	203	128	80.00	33.2	22.3	11.6	6.30
1.70	335	246	200	127	78.30	32.5	22.0	11.5	6.20
1.75	314	231	196	124	76.50	31.8	21.7	11.4	6.20
1.80	302	215	187	122	75.70	31.1	21.4	11.3	6.00




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 65-12


SMF VRLA RECHARGEABLE BATTERY

LONG
LIFE
SERIES


Discharge characteristic (25°C)



Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 75-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	20 Hour rate	80Ah
	10 Hour rate	75Ah
	5 Hour rate	67.5Ah
Internal Resistance (25°C, 100% Charge)		< 6.6 mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current		700A (5sec)
Maximum Charging current		22.5A
Short Circuit Current		1800A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
258 mm	166 mm	206 mm	215 mm	22.5 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	24h
1.60	240	178	137	81.8	50.20	21.8	14.3	7.67	3.52
1.65	222	169	131	78.3	47.50	21.4	14.1	7.65	3.50
1.70	206	158	122	77.0	46.90	21.0	13.9	7.6	3.48
1.75	195	151	117	73.6	45.30	20.6	13.5	7.55	3.46
1.80	180	139	112	73.1	98.60	19.8	13.3	7.5	3.43

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	24h
1.60	413	314	246	158.0	95.7	40.2	26.8	15.1	6.90
1.65	403	300	241	153	93.6	39.2	26.6	14.7	6.74
1.70	375	290	237	145	89.8	38.9	26.0	14.4	6.61
1.75	356	274	223	142	86.5	38.3	26.0	14.2	6.48
1.80	341	261	212	141	84.2	38.0	25.8	13.8	6.30




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 75-12


SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ES 80-12

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4





TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Seal Lead Acid Battery
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction (FR optional)
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output
- Wide Operating Temperature
- Maintenance-Free Operation

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	10 Years	
Capacity 25°C (77°F)	10 Hour rate	80Ah
	5 Hour rate	72Ah
	1 Hour rate	53.7Ah
Internal Resistance (25°C, 100% Charge)		6.5mΩ
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature		25°C ± 3°C
Maximum Discharge current (25°C)		750A (5sec)
Maximum Charging current		24A
Short Circuit Current		1900A
Charge Methods		14.4 to 14.7V
Constant Voltage Charge 77°F (25°C) - Cycle use		Temp. Compensation -30mV/°C
Charge methods		13.4 to 13.8V
Constant Voltage Charge 77°F (25°C) - Standby Use		Temp. Compensation -20mV/°C



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
350 mm	167 mm	179mm	179 mm	22.5 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	24h
1.60	247	188	149	87.3	53.70	22.7	15.0	8.20	3.72
1.65	233	178	137	83.0	51.60	22.5	14.7	8.15	3.70
1.70	218	168	132	80.3	49.80	22.4	14.7	8.1	3.65
1.75	204	159	126	77.6	47.10	21.8	14.4	8.05	3.63
1.80	190	149	118	75.0	46.30	20.7	14.1	8.00	3.61

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	5min	10min	15min	30min	1h	3h	5h	10h	24h
1.60	433	323	258	165	98.60	42.5	27.9	16.1	7.30
1.65	420	310	250	157	97.80	41.1	27.4	15.7	7.20
1.70	390	299	246	151	93.80	40.4	27	15.4	7.10
1.75	368	287	232	149	92.30	39.9	26.8	15.1	7.00
1.80	349	275	218	146	88.50	39.0	26.4	14.8	6.90




EnerRocketTM
CONTINUOUSLY SAFEGUARDING

ES 80-12


SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



v205.2



EnerRocket™

CONTINUOUSLY SAFEGUARDING

ESC 100-12 FR

SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22
BS6290-4
EUROBAT- HIGH Performance


TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output

CHARACTERISTICS

Nominal Voltage	12 V	
Design Life	12 Years	
Capacity (25°C)	10 Hour rate	100Ah
Internal Resistance (25°C, 100% Charge)	≤5.7 mΩ	
Self Discharge (20°C)	1 Month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature	25°C ± 3°C	
Maximum Discharge current (25°C)	500A (5sec)	
Maximum Charging current (25°C)	30A	
Short Circuit Current	2100A	
Charge Methods	14.4 to 14.7 V	
Constant Voltage Charge 77°F (25°C) - Cycle use	Temp. Compensation -30mV/°C	
Charge methods	13.4 to 13.8V	
Constant Voltage Charge 77°F (25°C) - Standby Use	Temp. Compensation -20mV/°C	



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
330mm	171mm	215mm	220mm	28.0 ± 3%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Voltage Volts/Cell	15min	20min	30min	1h	1.5h	2h	3h	4h
1.60	173	110	98.9	61.0	45.3	35.0	25.1	22.4
1.65	164	101	95.0	60.6	44.0	33.6	24.6	21.8
1.70	156	97	92.2	59.7	42.7	32.3	24.1	21.5
1.75	145	93	89.3	58.9	41.4	31.3	23.5	21.0
1.80	136	89	87.4	57.1	40.1	30.7	22.8	20.2

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Voltage Volts/Cell	15min	20min	30min	1h	1.5h	2h	3h	4h
1.60	304	202	198	119	84.3	68.2	48.4	41.9
1.65	299	195	187	117	82.7	67.0	47.8	40.8
1.70	290	190	182	116	80.2	65.8	47.3	40.0
1.75	279	183	176	112	78.2	64.6	46.7	38.1
1.80	270	178	170	109	76.3	63.9	45.9	37.4




EnerRocket™
CONTINUOUSLY SAFEGUARDING

ESC 100-12 FR


SMF VRLA RECHARGEABLE BATTERY

**LONG
LIFE
SERIES**


Discharge characteristic (25°C)




Constant voltage charging characteristic (0.25CA, 25°C)




Relationship between charging voltage and temperature




Self-discharge characteristic




Life characteristics of Standby use




Cycle service life in relation to depth of discharge



Temperature effects on float life



Temperature effects on capacity



Note:
GPSCG reserves the right to make changes to the above values without any notice.
All data and discharge characteristics are average values based on actual discharge cycle tests performed and not minimum values.

v205.1



EnerRocket™
CONTINUOUSLY SAFEGUARDING

ESH 12-820W FR

SMF VRLA RECHARGEABLE BATTERY

HIGH RATE
LONG
LIFE
SERIES

APPLICATIONS

UPS Systems
Telecommunication Systems
Fire Alarm Safety & Security Systems
Medical Equipment

COMPLIANCE STANDARDS

IEC 60896 PART 21 & 22

BS6290-4

EUROBAT- HIGH Performance



TECHNICAL FEATURES



- Non-Spillable Sealed Construction
- Absorptive Glass Mat System (AGM System)
- ABS (Acrylonitrile Butadiene Styrene) construction
- Gas Recombination
- Venting System for low internal pressure
- Low Self-Discharge
- Heavy-Duty, Highly Optimized Grids
- High Power Output

CHARACTERISTICS

Nominal Voltage	12V	
Design Life	12 Years	
Capacity (25°C)	15min 1.67ECV	820w
Internal Resistance(25°C, 100% Charge)	≤2.2mΩ	
Self Discharge (20°C)	1 month	Remaining Capacity 97%
Operating Temperature	Discharge	-20°C - 60°C
	Charge	-10°C - 60°C
	Storage	-20°C - 60°C
Normal Operating Temperature	25°C ± 3°C	
Maximum Discharge current (25°C)	1100A (5sec)	
Maximum Charging current (25°C)	69A	
Charge Methods Constant Voltage Charge 25°C Cyclic Use	14.4 to 14.7V	
	Temp.Compensation -30mV/°C	
Charge Methods Constant Voltage Charge 25°C Standby Use	13.4 to 13.8V	
	Temp. Compensation -20mV/°C	



SPECIFICATIONS

Length	Width	Height	Total Height	Weight (kg)
522mm	238mm	218mm	223mm	67.5 ± 5%

CONSTANT CURRENT DISCHARGE (Amperes) AT 25 °C

End Voltage Volt/Cell	3min	5min	10min	15min	20min	25min	30min	45min	60min
1.60V	971	748	558	447	389	341	303	222	171
1.65V	931	721	544	433	377	332	294	215	167
1.67V	915	711	538	428	372	328	291	212	165
1.70V	882	695	511	409	355	312	279	204	159
1.75V	876	675	486	390	337	296	267	194	151
1.80V	862	643	465	381	320	281	254	185	145

CONSTANT POWER DISCHARGE (Watts) AT 25 °C

End Voltage Volt/Cell	3min	5min	10min	15min	20min	25min	30min	45min	60min
1.60V	1486	1276	1018	827	683	601	534	394	305
1.65V	1451	1265	997	822	671	584	523	386	299
1.67V	1437	1261	984	820	667	578	519	383	297
1.70V	1402	1200	966	780	645	554	504	373	289
1.75V	1376	1138	907	752	621	531	488	362	281
1.80V	1347	1114	857	680	578	508	463	352	273











EnerRocket™
CONTINUOUSLY SAFEGUARDING

ESH 12-820W FR

SMF VRLA RECHARGEABLE BATTERY

HIGH RATE
LONG
LIFE
SERIES



Note:
GPSGC reserves the right to make changes to the above values without any notice.
All data and discharge characteristics are average values based on actual discharge cycle tests performed and not minimum values.

v205.2